

Dátový list pre produkt: DS188060-A

Stojanový rozdávateľ, 18U, š.800mm, hl.600mm, RAL7035 + RAL5005



SCHRACK-Info

TECHNICAL DATA

- The frame, the door, the side panels, the roof plate and the base plate are made of 1.0 mm sheet metal. The mounting for the optional castors is made of 2.0 mm sheet metal. All these parts are made of DC01 quality sheet steel. The vertical rails are made of galvanised sheet metal with a thickness of 2.0mm.
- Welded powder-coated sheet steel skeleton
- Height: 18U
- Width: 800mm
- Depth: 600mm
- Colour:
 - Light Grey RAL7035.
 - frame Blue RAL5005
- Maximum Load:
 - 15-22U: 300kg
 - 27-47U: 400kg
- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left.

- External hinge system allows up to 180 degree door opening angle.
- Glass doors can be replaced by optional DSRT doors (full metal or perforated, full width or double-wing).
- Removeable and lockable side-panels. Key included. For better passive cooling, side-panels can be replaced by optional perforated side-panels DSRS.
- Removeable and lockable rear-panel. Key included. Rear panel can be replaced by optional DSRT doors (glass, full or perforated metal, full width or double-wing) or by perforated rear-panel DSRR.
- 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DS enclosures, you can choose to adjust the 19" rails to a width of 21".
- In 900, 1.000 and 1.200 mm deep DS enclosures, there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories possible at the same time.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 35mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 35mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D400 – 310mm
 - W600 x D600 – 510mm
 - W600 x D800 – 710mm
 - W600 x D900 – 810mm
 - W600 x D1000 – 910mm
 - W600 x D1200 – 1110mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D400 – 375mm
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with opening, 19" punched. Flexible covered by removable plates of different heights to allow installation of fan-units and cable-entry panels. Remaining opening can be closed by use of one these plates.
 - D400 - Opening: 6U, Covering: 1 x 4U and 1 x 2U
 - D600 - Opening: 8U, Covering: 1 x 4U and 2 x 2U
 - D800 - Opening: 10U, Covering: 2 x 4U and 1 x 2U
 - D900 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1000 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1200 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
- Floor construction with opening, 19" punched. Covered by removable plate in full height.
 - D400 - Opening: 6U, Covering: 1 x 6U
 - D600 - Opening: 8U, Covering: 1 x 8U

- D800 - Opening: 10U, Covering: 1 x 10U
- D900 - Opening: 12U, Covering: 1 x 12U
- D1000 - Opening: 12U, Covering: 1 x 12U
- D1200 - Opening: 12U, Covering: 1 x 12U
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possible via roof, floor and rear panel. Delivered with demountable or break-out blanking plates.
- Brush strip panel for roof (DBK24800) optional.
- Air vents for passive ventilation.
- Earthing:
 - M8-Earthing point plus 19" - Earthingset in the rear of the cabinet
 - FastOn-Earthing-connections to all dismountable parts pre-installed
- Included assembly materials:
 - 16 x Cage nuts, bolts and washers M6
 - 4 x Levelling feet
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, doors, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Technické informácie

Šírka (mm)	800,00
Výška (mm)	900,00
Hĺbka (mm)	600,00
Hmotnosť (kg)	45,30
Min. teplota okolia (°C)	0
Max. teplota okolia (°C)	40
Určené pre U	18U-900mm
Farba	RAL 7035 / RAL 5005 (light grey / blue)

Tabuľka objednávacích čísel

POPIS	OBJ. ČÍSLO
Stojanový rozvádzač, 18U, š.800mm, hl.600mm, RAL7035 + RAL5005	DS188060-A
Voliteľné príslušenstvo	
Vložka polcylindrického zámku 333, EMKA s jedným kľúčom vrátane 1x zapustenej skrutky M5x16mm V2A	DV900333S
Horný/spodný vstupný kábl.panel s protiprach.kefou, 2U	DBK24800
Horná/spodná ventil.jednotka, 2x ventilátor, termostat, 4U pre voľne stojace rozvádzače DS/DSZ a DSS	DLT44802-A
Bočný panel (pár) podstavca pre rozvádzač DS, hl. 600mm	DSOT1260

Tabuľka objednávacích čísel

POPIS	OBJ. ČÍSLO
Voliteľné príslušenstvo	
Pred./zad.panel podstavca,perf.+protiprachový filter,š.800mm pre stojanový rozvádzač, RAL7035	DSOF1283
19" vyvážovací panel,5x veľké kov. oko, 1 U, farba šedá	DBC14805
19" vyvážovací panel, 5x veľké plastové oko, 1 U, farba šedá	DBK14805
19"pevná perf.polica skrutk.,hl.450mm,záťaž 80kg, 1 U,RAL7035	DFS14845-C
Napájací panel PDU 19", 9x SCHUKO, 1 U, kábel 3 m	IU070114-3
19" napájací panel 7x230V,2m kábel,typ Schuko, SPD,výška 1 U 2m prírodný kábel, RAL7035	IU070113
19" PDU, 9x Schuko, 1 U, 2m-cable, vypínač, čierny, , ALU hliníkový profil	Q7070114-A
19" PDU, 7x Schuko, Switch, Overvoltage protection, 1 U 2m prírodný kábel	Q7070113-A
Zásuv.panel pas. IN: 400V 16A CEE červ. OUT: 12xC13,6xSch	HSMPP312
Držiak vertikál. PDU pre 800mm DS a DSZ rozvádzače, 1 U 1 pár = 2 kusy, montáž na vonkajšiu stranu 19" lišty, vrátane montážneho materialu	DSPDU010
Montážna sada M6, 50x matica, skrutka, podložka	DSSRA050
19" montážna platňa, 14U, oceľová, perforovaná vrátane skrutiek a klieťkových matíc	DMP1914
Osvetl. jednotka LED, magnet, 230V AC, s dverným spínačom zapnutá po otvorení dvier rozvádzača	DTLIGHT01
Switch 24xRJ45 10/100/1000, tichý, interná nap. jed., 19" bez ventilátora, kovové šasi	QLGSW2457
19" patchpanel pre 24 modulov (SFA/SFB) neosadený 1 U RAL7035 svetlosivý	HSE0240GS