

Dátový list pre produkt: DSP376065-

Stojanový rozdávateľ, 37U, š.600mm, hl.600mm, PCIP54 RAL7035/5006



SCHRACK-Info

Application

Enclosure for Input-Devices and Display of Control-Units or Computer with Keyboard, Mouse and Monitor. To be used in production halls or similar environments. Special construction for rough, dusty environments, if installed equipment is worth to be especially protected and/or equipment needs special protection due to environmental conditions (dust, humidity). The installed equipment is often the central station for the production machinery. Best availability of the (production-) machinery is achieved due to the special protection of the installed equipment against dust and humidity (Protection IP54). Machinery down-time due to defect of central station because of dust or humidity is avoided. The lockable departments of the enclosure provide protection against unauthorized access.

TECHNICAL DATA

- Steel sheet
 - Dimensions:
 - Height: 1750 mm
 - Width: 600 mm
 - Depth: 600 mm
- Color:
 - Doors, Side- and Back-panel:
 - light grey RAL 7035
 - Frame: Blue RAL 5005

- Max. Load: 400 kg
- IP Rating: IP 54
 - All doors, rear- and sidepanels are sealed, which ensures protection against dust and humidity.
 - Enclosure is without perforation.
- Ventilation: Cooled by sharing heat with environment via chassis.
- Rear- and side-panels: Fixed to frame by screws. Demountable.
- Cable Entry: 300x100 mm at the bottom. Covered by a sealed and screwed blanking panel. Method of cable leading inside the enclosure must correspond to requested IP protection level against dust and humidity.
- Earthing:
 - M8-Earthing point plus 19" Earthing-set.
 - FastOn-Earthing-connections to all dismountable parts pre-installed.
- Departments: 3
 - Separation of upper and lower departments by pre-installed 350 mm deep sliding shelf for keyboard and mouse.
 - Cable-guiding in rear part of the enclosure.
 - Vertical cable-management can be flexibly organized by use of optional cable-organizers DBKO8080.
- Bottom department:
 - Used for control-unit or computer
 - 21 U / 934 mm
 - Fullmetal door RAL 7035. Swinghandle with halfcylinder. Same key as other locks. Halfcylinder can be changed. Door can be opened 180°. Hinged right.
 - Two pairs of vertical 19" rails. 21U. Continuously depth-adjustable.
- Middle department:
 - Used for input-device or keyboard and mouse.
 - 4U / 178 mm
 - Fullmetal door RAL 7035, folding, single point lock. Same key as other locks.
 - Sliding shelf W=460 mm, D=350 mm for keyboard and mouse pre-installed. Usable depth if fully drawn out: 240 mm.
 - Mouse-shelf W=150 mm, D=170 mm can be drawn out under right side of keyboard shelf.
 - Keyboard and mouse not included in delivery.
- Top department:
 - Used for display-device or computer monitor.
 - 12U / 534 mm
 - Glasdoor, 4 mm safety glass, RAL 7035. Swinghandle with halfcylinder. Same key as other locks. Halfcylinder can be changed. Door can be opened 180°. Hinged right.
 - Two pairs of vertical 19" rails. 12U. Continuously depth-adjustable.
 - Optional a fixed shelf with 350 mm (DFS 14835-C), 450 mm (DFS 14845-C) or 550 mm (DFS 14855-C) depth can be installed to put display devices or computer monitors on it.
- Distances (valid for bottom and top department):
 - Space between front vertical 19" rail and door glass at max. spacing: 35 mm
 - Space between rear vertical 19" rail and rear panel at max. spacing: 35 mm
 - Maximum distance between vertical rails (19" rails): 510 mm
 - Maximum usable depth in free-standing cabinets when installed e.g. on shelves: 575 mm
 - Spacing between vertical 19" rails: 451 mm
- Including assembly materials: 16x Cage nuts, bolts and washers M6.
- Wide range of available accessories (fixed and sliding shelves, fan-units, base, patch panels, cable management, PDUs, light-unit, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Technické informácie

Šírka (mm)	600,00
Výška (mm)	1.750,00
Hĺbka (mm)	600,00
Hmotnosť (kg)	84,70
Min. teplota okolia (°C)	-10
Max. teplota okolia (°C)	70
Určené pre U	37U-1750mm

Tabuľka objednávacích čísel

POPIS	OBJ. ČÍSLO
Stojanový rozvádzač, 37U, š. 600mm, hl. 600mm, PCIP54 RAL7035/5006	DSP376065
Voliteľné príslušenstvo	
19" vyvážovací panel, 5x veľké kov. oko, 1U, farba šedá	DBC14805
19" vyvážovací panel, 5x veľké plastové oko, 1U, farba šedá	DBK14805
19" pevná perf. polica skrutk., hl. 450mm, záťaž 80kg, 1U, RAL7035	DFS14845-C
Napájací panel PDU 19", 9x SCHUKO, 1U, kábel 3 m	IU070114-3
19" napájací panel 7x230V, 2m kábel, typ Schuko, SPD, výška 1U 2m prívodný kábel, RAL7035	IU070113
19" PDU, 9x Schuko, 1U, 2m-cable, vypínač, čierny, ALU hliníkový profil	Q7070114-A
19" PDU, 7x Schuko, Switch, Overvoltage protection, 1U 2m prívodný kábel	Q7070113-A
Montážna sada M6, 50x matica, skrutka, podložka	DSSRA050
19" montážna platňa, 14U, ocelová, perforovaná vrátane skrutiek a kliečkových matíc	DMP1914
Osvetl. jednotka LED, magnet, 230V AC, s dverným spínačom zapnutá po otvorení dvier rozvádzača	DTLIGHT01
Switch 24xRJ45 10/100/1000, tichý, interná nap. jed., 19" bez ventilátora, kovové šasi	QLGSW2457
19" patchpanel pre 24 modulov (SFA/SFB) neosadený 1U RAL7035 svetlosivý	HSER0240GS