


Dátový list pre produkt: DSZ426020-

Stojanový rozvádzač rozoberateľný 42U, š. 600mm, hl.1200mm



SCHRACK-Info

- Powder-coated sheet steel skeleton 1,5mm
- Height: 42U
- Width: 600mm
- Depth: 1.200mm
- Demountable Parts:
 - Front Part: 105mm
 - Rear Part: 105 mm
- Main Part welded:
 - 390mm at 600 deep enclosure
 - 590mm at 800 deep enclosure
 - 690mm at 900 deep enclosure
 - 790mm at 1.000 deep enclosure
 - 990mm at 1.200 deep enclosure
- Colour: Light Grey RAL 7035,
- Frame Blue RAL 5005
- Maximum load:
 - 15 – 22U: 300 kg
 - 27 – 47 U: 400kg
- Degree of protection: IP20

- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left .
- External hinge system allows up to 180 degree door opening angle.
- Front glass door can be replaced by optional DSRT metal door (full metal or perforated).
- Removeable and lockable rear and side panels. Key included.
- Rear panel can be replaced by optional DSRT rear door. Glass- or metal door (full metal or perforated). 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DSZ enclosures, you can choose to adjust the 19" rails to a width of 21" .
- In 900, 1.000 and 1.200 mm deep DSZ enclosures there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories at the same time possible.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 43mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 45mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D600 – 494mm
 - W600 x D800 – 694mm
 - W600 x D900 – 794mm
 - W600 x D1000 – 894mm
 - W600 x D1200 – 1.094mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1.070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1.175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with 19" punching.
- 600 mm deep DSZ enclosures come with 8U deep roof aperture, flexible covering with 1 x 4U and 2 x 2U cover plates.
- 800 mm deep DSZ enclosures come with 10U deep roof aperture, flexible covering with 2 x 4U and 1 x 2U cover plates.
- 1.000 and 1.200 mm deep DS enclosures come with 12U deep roof aperture, flexible covering with 2 x 4U and 2 x 2U cover plates.
- Floor construction with 19" punching.
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possibility via roof, floor and rear panel. Delivered with blanking plates.
- Brush strip cable entry panel for roof (DBK24800) optional available.
- Air vents for passive ventilation Fully pre-wired earthing.
- Includes M8 earthing point and earthing kit. Including assembly materials: 24 x Cage nuts, bolts and washers M6, 4 x Levelling feet.

- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Technické informácie

Šírka (mm)	600,00
Výška (mm)	1.970,00
Hĺbka (mm)	1.200,00
Hmotnosť (kg)	110,80
Min. teplota okolia (°C)	0
Max. teplota okolia (°C)	40
Určené pre U	42U-1970mm
Farba	RAL 7035 / RAL 5005 (light grey / blue)

Tabuľka objednávacích čísel

POPIS	OBJ. ČÍSLO
Stojanový rozvádzač rozoberateľný 42U, š. 600mm, hl.1200mm	DSZ426020
Voliteľné príslušenstvo	
Vložka polcylindrického zámku 333, EMKA s jedným kľúčom vrátane 1x zapustenej skrutky M5x16mm V2A	DV900333S
Horný/spodný vstupný kábl.panel s protiprach.kefou, 2U	DBK24800
Horná/spodná ventil.jednotka, 2x ventilátor, termostat, 4U pre voľne stojace rozvádzače DS/DSZ a DSS	DLT44802-A
Bočný panel (pár) podstavca pre rozvádzač DS, hl. 1200mm	DSOT1220
Pred./zad.panel podstavca,perf.+protiprachový filter,š.600mm pre stojanový rozvádzač, RAL7035	DSOF1263
19" vyvážovací panel,5x veľké kov. oko, 1U, farba šedá	DBC14805
19" vyvážovací panel, 5x veľké plastové oko, 1U, farba šedá	DBK14805
19"pevná perf.polica skrutk.,hl.450mm,záťaž 80kg, 1U,RAL7035	DFS14845-C
Napájací panel PDU 19", 9x SCHUKO, 1U, kábel 3 m	IU070114-3
19" napájací panel 7x230V,2m kábel,typ Schuko, SPD,výška 1U 2m prívodný kábel, RAL7035	IU070113
19" PDU, 9x Schuko, 1U, 2m-cable, vypínač, čierny. , ALU hliníkový profil	Q7070114-A
19" PDU, 7x Schuko, Switch, Overvoltage protection, 1U 2m prívodný kábel	Q7070113-A

Tabuľka objednávacích čísel

POPIS	OBJ. ČÍSLO
Voliteľné príslušenstvo	
Montážna sada M6, 50x matica, skrutka, podložka	DSSRA050
19" montážna platňa, 14U, ocelová, perforovaná vrátane skrutiek a klieťkových matíc	DMP1914
Osvetl. jednotka LED, magnet, 230V AC, s dverným spínačom zapnutá po otvorení dvier rozvádzača	DTLIGHT01
Switch 24xRJ45 10/100/1000, tichý, interná nap. jed., 19" bez ventilátora, kovové šasi	QLGSW2457
19" patchpanel pre 24 modulov (SFA/SFB) neosadený 1U RAL7035 svetlosivý	HSER0240GS