


Dátový list pre produkt: HLP23LT03F

Opt.prep.kábel duplex LC/UPC - ST/UPC, 50/125µm OM3, LSOH

aqua, 3.0m



SCHRACK-Info

Multimode patch cords are mainly used for short-distance communication with high transmission rates, for example within a building or on a campus. The multimode patch cords are equipped with an LSOH-jacket. These comply with IEC or EIA-TIA standards. These multimode enhanced patch cords are terminated with optimized connectors which give optimum optical performance.

FEATURES

- LC/UPC - ST/UPC connectors
- Low smoke zero halogen (LSOH) jacket
- 900 µm tight buffer
- Multimode cabled fiber conforms to ITU-T G.651.1, IEC 60793-2-10
- Duplex
- REACH, RoHS and SvHC materials compliant

APPLICATIONS

- CATV / Video
- Passive Optical Network PON
- WDM / DWDM
- FTTH
- Data centers
- Supports high speed multi channel video, data and voice services in metropolitan and access networks


- ATM, SONET and WDM



Technické informácie

Normy	IEC 61300-3-4 / IEC 61300-3-6
Norma konektora	IEC 61754
Kombinácia konektorov	LC/ST
Dĺžka patch kábla (m)	3
Vlákno	50/125μ OM3 multimód
Plášť kábla	LS0H
Farba	aqua
Typický útlm (dB)	≤0,25
Typický spätný útlm (dB)	≥30
Min. teplota okolia (°C)	-20
Max. teplota okolia (°C)	60
Šírka (mm)	210,00
Výška (mm)	320,00
Hmotnosť (kg)	0,14

Rozmerový obrázok: Opt.prep.kábel duplex LC/UPC - ST/UPC, 50/125μm OM3, LS0H



POPIS

OBJ. ČÍSLO

Opt.prep.kábel duplex LC/UPC - ST/UPC, 50/125µm OM3, LSOH
aqua, 3.0m

HLP23LT03F