



Dátový list pre produkt: HSELS48SLP

Optická vaňa, 48 vlákien, LC 50/125µm OM5, 19", 1U, trieda C

podľa IEC 61753-1, RAL7035, vysúvacie, CLASSIC



Schrack-Info

These spliceboxes are delivered assembled with already installed couplers and enclosed pigtails (all connectors come with ceramic ferrule).

The spliceboxes are depth-adjustable using the two 19" brackets.

The spliceboxes have one, two or four splice trays depending on the number of fibres with integral splice organisers for shrink-on splice protectors and is designed for up to 4 cable entries, equipped with one M20 cable entry by default.

Blind covers are used to close off unused cable entry ports.

Two versions for up to 48 fibres in a sliding tray design are available:

- with 24 LC-Duplex couplers
- with 24 SC-Duplex couplers
- Material: zinc-coated steel
- Installation: 19", 1U
- Dimensions W x H x D: 483 x 44 x 240mm
- Housing color: RAL7035 Light grey
- Color of couplers (LC and SC): Lime-green
- Dustcovers (LC and SC): Included

Technické informácie

Šírka (mm)

480,00

Technické informácie - Pokračovanie

Výška (mm)	44,00
Hĺbka (mm)	242,00
Hmotnosť (kg)	2,53
Vlákno	50/125 μ OM5 multimód
Farba	RAL 7035 (svetlošedá)
Typický útlm (dB)	< 0,2
Typický spätný útlm (dB)	> 35
Min. teplota okolia (°C)	-10
Max. teplota okolia (°C)	70
Počet vlákien	48

Tabuľka objednávacích čísel

POPIS	OBJ. ČÍSLO
Optická vaňa, 48 vlákien, LC 50/125µm OM5, 19", 1U, trieda C podľa IEC 61753-1, RAL7035, vysúvacie, CLASSIC	HSELS48SLP
Voliteľné príslušenstvo	
Ochrana zvarov 60mm, 10 ks LVZ0007	HELSP00011
Ochrana zvarov 40mm, balenie 10 ks LVZ0006	HELSP00010
Čistiace pero na optické konektory LC a MU Vhodné pre konektory UPC a APC. Viac ako 1 000 čistiacich cyklov.	HSELSZT001
Opt. hladinomer s integrovaným laserovým zdrojom svetla(VFL) Test medeného kábla RJ45. POZOR: Toto je laserový výrobok triedy 2. Nepozerajte sa do lúča. Vždy majte kryt na porte VFL, keď sa nepoužíva. Pri práci s optickými systémami sa odporúča používať ochranné okuliare proti laseru.	HSELSZT003
Opt.prep.kábel duplex LC/UPC - LC/UPC, 50/125µm OM5, LS0H limetkový zelený, 0.5m	HLP2SLL00F
Opt.prep.kábel duplex LC/LC, 50/125µm OM5, LS0H-3, 2.0m limetkovo-zelený	HLP2SLL02F
Opt.prep.kábel duplex LC/LC, 50/125µm OM5, LS0H-3, 5.0m limetkovo-zelený	HLP2SLL05F