

Dátový list pre produkt: SR3PDIEM04

PDU Essential Metered; 4xC13; 2xC19; 230V; 16A

Messung pro Phase, inkl. Befestigungswinkel mit Schrauben



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/230V | 3,6kW
- Output: 4xC13 0° IEC Socket 2xC19 90° IEC Socket
- Power Supply: with C20 Built-In Connector
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technické informácie

Dĺžka/hĺbka (mm)	437,40
------------------	--------

Technické informácie - Pokračovanie

Šírka (mm)	45,00
Výška (mm)	60,00
Hmotnosť (kg)	1,00
EAN kód	4057298233050
Cena	754,60
Min. teplota okolia (°C)	-5
Max. teplota okolia (°C)	45
Menovité napätie	230V
Krytie	IP20
Typ produktu	Metered Essential
Počet zásuviek	6
Typ zásuvky	4 x IEC320 C13 und 2 x IEC320 C19
Menovitý prúd (A)	16
Fázy na jedno napájanie	1
Typ pripojenia	C20
Protokol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Montáž	Úchyt (tvar L)

POPIS	OBJ. ČÍSLO
PDU Essential Metered; 4xC13; 2xC19; 230V; 16A Messung pro Phase, inkl. Befestigungswinkel mit Schrauben	SR3PDIEM04