

Dátový list pre produkt: SR3PDIEM05

PDU Essential Metered; 24xC13; 3xC19; 230V; 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/230V | 3,6kW
- Output: 24xC13 0° IEC Socket 3xC19 90° IEC Socket
- Supply cable: 3.0m | 2,5mm²
- with CEE 16A plug, blue
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technické informácie

Technické informácie - Pokračovanie

Dĺžka/hĺbka (mm)	1.000,00
Šírka (mm)	45,00
Výška (mm)	60,00
Hmotnosť (kg)	2,80
EAN kód	4057298233067
Cena	868,10
Min. teplota okolia (°C)	-5
Max. teplota okolia (°C)	45
Menovité napätie	230V
Krytie	IP20
Typ produktu	Metered Essential
Počet zásuviek	27
Typ zásuvky	24 x IEC320 C13 und 3 x IEC320 C19
Menovitý prúd (A)	16
Fázy na jedno napájanie	1
Typ pripojenia	CEE 16 A
Protokol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Montáž	Úchyt (tvar L)

POPIS	OBJ. ČÍSLO
PDU Essential Metered; 24xC13; 3xC19; 230V; 16A	
Measurement per phase, incl. mounting bracket with screws	SR3PDIEM05