

Dátový list pre produkt: SR3PDIEM09

PDU Essential Metered; 24xC13; 6xC19; 400V; 32A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 32A/400V | 22kW
- Output: 24xC13 0° IEC Socket 6xC19 90° IEC Socket
- 6xMiniature Circuit Breaker C16A
- split into three phases, each phase split into two blocks, each block fused with a MCB
- Supply cable: 3.0m | 4mm²
- with CEE 32A plug, red
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technické informácie

Dĺžka/hĺbka (mm)	1.756,08
Šírka (mm)	45,00
Výška (mm)	94,00
Hmotnosť (kg)	5,40
EAN kód	4057298233111
Cena	1.382,00
Min. teplota okolia (°C)	-5
Max. teplota okolia (°C)	45
Menovité napätie	400V
Krytie	IP20
Typ produktu	Metered Essential
Počet zásuviek	30
Typ zásuvky	24 x IEC320 C13 und 6 x IEC320 C19
Menovitý prúd (A)	32
Fázy na jedno napájanie	3
Typ pripojenia	CEE 32 A
Protokol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Montáž	Úchyt (tvar L)

POPIS	OBJ. ČÍSLO
PDU Essential Metered; 24xC13; 6xC19; 400V; 32A	
Measurement per phase, incl. mounting bracket with screws	SR3PDIEM09