

Dátový list pre produkt: SR3PDIPM01

PDU PRO Metered, 16xC13, 4xC19, 230V, 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 16 A / 230 V | 3,6 kW
- Supply cable: 3,0 m | 2,5 mm²
- mit CEE plug 16 A blue
- Output: 16 x C13 IEC Socket + 4 x C19 IEC Socket
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)
- Packed in cardboard box
- Length 1076 mm

Technické informácie

Dĺžka/hĺbka (mm)	1.076,00
Šírka (mm)	56,00
Výška (mm)	70,00
Hmotnosť (kg)	3,00
EAN kód	4057298202872
Cena	1.464,00
Min. teplota okolia (°C)	0
Max. teplota okolia (°C)	50
Menovité napätie	230V
Krytie	IP20
Typ produktu	Metered
Počet zásuviek	20
Typ zásuvky	16 x IEC320 C13 und 4 x IEC320 C19
Menovitý prúd (A)	16
Fázy na jedno napájanie	1
Typ pripojenia	CEE 16 A
Protokol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Montáž	Úchyt (tvar L)

POPIS	OBJ. ČÍSLO
PDU PRO Metered, 16xC13, 4xC19, 230V, 16A	SR3PDIPM01
Measurement per phase, incl. mounting bracket with screws	