

Dátový list pre produkt: SR3PDIPM02

PDU PRO Metered, 16xC13, 4xC19, 230V, 16A, RCM

Measurement per phase, Residual Current Monitoring per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered RCM
- Metering per phase
- Residual Current Monitoring per phase, Typ B
- Input: 16 A / 230 V | 3,6 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A blue
- Output: 16x C13 IEC Socket + 4 x C19 IEC Socket
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

- Packed in cardboard box
- Length 1119 mm

Technické informácie

Dĺžka/hĺbka (mm)	1.118,70
Šírka (mm)	56,00
Výška (mm)	70,00
Hmotnosť (kg)	3,04
EAN kód	4057298207860
Cena	1.632,00
Min. teplota okolia (°C)	0
Max. teplota okolia (°C)	50
Menovité napätie	230V
Krytie	IP20
Typ produktu	Metered
Počet zásuviek	20
Typ zásuvky	16 x IEC320 C13 und 4 x IEC320 C19
Menovitý prúd (A)	16
Fázy na jedno napájanie	1
Typ pripojenia	CEE 16 A
Protokol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Montáž	Úchyt (tvar L)

POPIS

OBJ. ČÍSLO

PDU PRO Metered, 16xC13, 4xC19, 230V, 16A, RCM

SR3PDIPM02

Measurement per phase, Residual Current Monitoring per phase, incl. mounting bracket with screws