

Dátový list pre produkt: SR3PDIPP04

PDU PRO Metered+, 36xCombo (C13,C15,C19,C21), 400V, 16A, RCM

Metering per outlet, Residual Current Monitoring per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered+ inkl. RCM
- Metering per socket
- Residual Current Monitoring per phase, Typ B
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 36x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </I

Technické informácie

Dĺžka/hĺbka (mm)	1.696,50
Šírka (mm)	56,00
Výška (mm)	71,00
EAN kód	4057298230332
Cena	4.007,00
Min. teplota okolia (°C)	0
Max. teplota okolia (°C)	50
Menovité napätie	400V
Krytie	IP20
Typ produktu	Metered+
Počet zásuviek	36
Typ zásuvky	36 x Combo Socket (C13/C15/C19/C21)
Menovitý prúd (A)	16
Fázy na jedno napájanie	3
Typ pripojenia	CEE 16 A
Protokol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Montáž	Úchyt (tvar L)

POPIS	OBJ. ČÍSLO
PDU PRO Metered+, 36xCombo (C13,C15,C19,C21), 400V, 16A, RCM	
Metering per outlet, Residual Current Monitoring per phase, incl. mounting bracket with screws	SR3PDIPP04