

Dátový list pre produkt: SR3PDIPS03

PDU PRO Switched, 18xCombo (C13, C15, C19, C21), 24xC13, 400V, 16A

Measurement per phase (measurement at socket level can be upgraded with license),
switchable per socket, includes mounting bracket with screws



SCHRACK-Info

- PDU PRO Switched
- Metering per phase/line
- Can be upgraded to measuring per socket at any time via licence (SR3PAB0011, SR3PAB0012, SR3PAB0013)
- switchable sockets
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 24x C13 IEC Socket + 18x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)

- Incl. mounting brackets (L-shaped) </l

Technické informácie

Dĺžka/hĺbka (mm)	1.678,20
Šírka (mm)	56,00
Výška (mm)	71,00
EAN kód	4057298230523
Cena	3.960,00
Min. teplota okolia (°C)	0
Max. teplota okolia (°C)	50
Menovité napätie	400V
Krytie	IP20
Typ produktu	Switched
Počet zásuviek	42
Typ zásuvky	24 x IEC320 C13 + 18 x Combo Socket (C13/C15/C19/C21)
Menovitý prúd (A)	16
Fázy na jedno napájanie	3
Typ pripojenia	CEE 16 A
Protokol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Montáž	Úchyt (tvar L)

POPIS	OBJ. ČÍSLO
PDU PRO Switched, 18xCombo (C13,C15,C19,C21),24xC13, 400V, 16A Measurement per phase (measurement at socket level can be upgraded with license), switchable per socket, includes mounting bracket with screws	SR3PDIPS03